Produktblatt | product information sheet

2010

teslanol®



Isolier- und Schutzlack-Spray

- Anwendung:
  Klarer Schutzlack zum Versiegeln und Isolieren von gedruckten Schaltungen, Spulen und sonstigen elektronischen Bauelementen, elektrischen Anlagen wie Verteilern, Batterien, Motoren. Verhindert Kriechströme, beseitigt Feinschlüsse an Spulen und Transformatoren.
- Eigenschaften:
  Transparent, frequenz- und spannungsstabil (Eigenwiderstand 22 kV bei Schichtstärke 25 µ). Durchlötbar; säure-, salz- und kondenswasserbeständig. Tropft nicht und verläuft gleichmäßig.

Protective lacquer

- *Application:*
  Clear protective lacquer for sealing and insulating circuits, coils and other electronic components, electrical systems such as distributors, batteries, motors. Prevents leak currents and eliminates leaks in coils and transformers.
- *Properties:*
  Transparent, withstands fluctuations in frequencies and voltages (22 kV input resistance at 25 µ layer thickness), can be soldered through, is resistant to acids, salted and condensed water. Will not drop and spreads evenly.

26027	**Isolier- und Schutzlack-Spray**	200 ml	12 Dosen | *cans*
26028	**Isolier- und Schutzlack-Spray**	400 ml	12 Dosen | *cans*

teslanol-Distributor: wentronic Electronic Components Handels GmbH ·Pillmannstraße 12 · 38112 Braunschweig ·Germany
Fon +49 531-21058-0 · Fax +49 531-21058-22 · office@wentronic.com · www.wentronic.com